

Glazing of partition panels

GLAZING IN PLASTERBOARD PARTITIONS



With the system of partition panels, a glazed window panel represents one of the basic elements to construct clean workplaces and areas with maximum safety, sterility, hygiene, easy maintenance and sanitation.

The system in question is the PHARMA glazing system, offering double-sided glazing where the glass pane is in plane with the surface of the panel. Its design makes it suitable especially for hospital environments, areas in pharmaceutical industry, electrical engineering industry, mechanical engineering industry, food industry, etc.

MORE INFORMATION, PHOTOS



TECHNICAL DATA

Type Glazing in plasterboard partitions

www.blockcrs.com

Panel thickness
100 mm
125 mm
150 mm
75 mm

Structural opening dimensions	
width	height
1000 mm	1200 mm
1000 mm	1500 mm
1200 mm	1200 mm
1200 mm	1500 mm
800 mm	1200 mm
800 mm	1500 mm

Maximum dimensions of nominal opening AxB is 1500x1500mm! Min. width 560 mm, max. dimension 1500 mm. Min. height 800 mm, max. dimension 1500 mm.

Glazing

laminated safety glass, thickness 6 mm

float glass, thickness 4 mm

atypical

Note: As standard the glazing is of clear glass, but it is possible to order an atypical version with milk glass. Float glass design only for glazing with sill 1100mm and above.

metal sheet, hue RAL 9002 metal sheet, hue RAL 9016 Stainless steel AISI 304 FIN 8
Stainless steel AISI 304 FIN 8
metal sheet, hue RAL
Atypical design
Type design
Atypical design
Type design 0 - Unique specification out of offered versions Atypical design Q - atypical design that cannot be uniquely specified by a code

www.blockcrs.com Changes may be made as a result of technical progress or improvements in services offered | Update 21.02.2020 | 2/2